



WELDING OSCILLATOR



Features :-

Provides smooth, stable, & precise Oscillating Movement of the Welding Torch. Increases sidewall fusion, eliminates undercut.

Increases productivity for multi-pass welds.

Improves weld quality & appearance.

Compatible with PTA, GTAW, PAW, GMAW, FCAW, & SAW weld processes.

Independent dwell settings & speed settings for each side.

TECHNICAL SPECIFICATIONS

Stroke Width	0 - 25 mm in step of 0.2 mm
Stroke Speed 1	0 - 3000 mm per minute
Number of Stroke	0 - 60 per minute
Left Dwell	0 - 9.9 sec
Right Dwell	0 - 9.9 sec
Input Supply	230 Volts

TECHNOCRATS PLASMA SYSTEMS PVT. LTD.



Corporate Office & Works : Nirav 2, Gaon Devi Indl. Complex, Sativali, Vasai (East), Dist. Thane - 401 208. Tel :- 0250-2481511 / 2481512 / 2481513. Mobile :- 09320033114.

Regd. Office :- 310, Tapo Commercial Centre, Ram Mandir Road, Goregaon (West), Mumabi 400 104. Tel :- 022 - 26763513 / 26763514 / 26764048.

E-mail : sales@technocratplasma.com • Website : www.technocratplasma.com